

# S5243 Specifications<sup>1</sup>



## Primary Specifications

Impedance	50 Ohm
Test port connector	NMD 2.4 mm, male
Number of test ports	2
Frequency range	10 MHz to 43.5 GHz
Full frequency accuracy	$\pm 2 \cdot 10^{-6}$
Frequency resolution	1 Hz
Number of measurement points	2 to 500,001
Measurement bandwidths (with 1/1.5/2/3/5/7 steps)	1 Hz to 2 MHz
Dynamic range <sup>2</sup>	
10 MHz to 8 GHz	135 dB (140 dB typ.)
8 GHz to 43.5 GHz	125 dB (130 dB typ.)

## Measurement Accuracy

Accuracy of transmission measurements <sup>4</sup>	Magnitude / Phase
10 MHz to 8 GHz	
0 dB to +10 dB	$\pm 0.2$ dB / $\pm 2^\circ$
-55 dB to 0 dB	$\pm 0.1$ dB / $\pm 1^\circ$
-75 dB to -55 dB	$\pm 0.2$ dB / $\pm 2^\circ$
-95 dB to -75 dB	$\pm 1.0$ dB / $\pm 6^\circ$
8 GHz to 43.5 GHz	
0 dB to +10 dB	$\pm 0.2$ dB / $\pm 2^\circ$
-45 dB to 0 dB	$\pm 0.1$ dB / $\pm 1^\circ$
-65 dB to -45 dB	$\pm 0.2$ dB / $\pm 2^\circ$
-85 dB to -65 dB	$\pm 1.0$ dB / $\pm 6^\circ$
Accuracy of reflection measurements <sup>5</sup>	Magnitude / Phase
10 MHz to 26.5 GHz	
-15 dB to 0 dB	$\pm 0.5$ dB / $\pm 5^\circ$
-25 dB to -15 dB	$\pm 1.5$ dB / $\pm 10^\circ$
-35 dB to -25 dB	$\pm 5.5$ dB / $\pm 30^\circ$
26.5 GHz to 43.5 GHz	
-15 dB to 0 dB	$\pm 0.6$ dB / $\pm 6^\circ$
-25 dB to -15 dB	$\pm 2$ dB / $\pm 12^\circ$
-35 dB to -25 dB	$\pm 7.5$ dB / $\pm 35^\circ$
Trace noise magnitude (IF bandwidth 3 kHz)	
10 MHz to 43.5 GHz	0.004 dB rms
Temperature dependence	
10 MHz to 6 GHz	0.02 dB/°C
6 GHz to 43.5 GHz	0.04 dB/°C

[1] All specifications subject to change without notice. [2] The dynamic range is defined as the difference between the specified maximum power level and the specified noise floor. The specification applies at 10 Hz IF bandwidth. [3] Reflection and transmission measurement accuracy applies over the temperature range of  $(73 \pm 9)^\circ\text{F}$  or  $(23 \pm 5)^\circ\text{C}$  after 40 minutes of warming-up, with less than  $1^\circ\text{C}$  deviation from the full two-port calibration temperature, at output power of -10 dBm. Frequency points have to be identical for measurement and calibration (no interpolation allowed). [4] Transmission specifications are based on a matched DUT, and IF bandwidth of 10 Hz. [5] Reflection specifications are based on an isolating DUT. [6] Specification applies over entire frequency range at output power of 0 dBm. © Copper Mountain Technologies - [www.coppermountaintech.com](http://www.coppermountaintech.com) - Rev. 2020Q3

# S5243 Specifications<sup>1</sup>

## Effective System Data

10 MHz to 26.5 GHz	
Directivity	42 dB
Source match	34 dB
Load match	42 dB
Reflection tracking	±0.15 dB
Transmission tracking	±0.08 dB

## Uncorrected System Performance

10 MHz to 43.5 GHz	
Directivity	10 dB
Source match	10 dB
Load match	10 dB

## Test Port Output

Power range	-50 dBm to 0 dBm
Power accuracy	±1.5 dB
Power resolution	0.05 dB
Harmonic distortion <sup>6</sup>	-10 dBc
Non-harmonic spurious <sup>6</sup>	-10 dBc

## Test Port Input

Noise floor	
10 MHz to 8 GHz	145 dBm/Hz (150 dBm/Hz typ.)
8 GHz to 43.5 GHz	135 dBm/Hz (140 dBm/Hz typ.)
Damage level	+23 dBm
Damage DC voltage	15 V

## Measurement Speed

Time per point	15 µs typ.
Port switchover time	0.2 ms

## Frequency Reference Input

Port	10 MHz Ref In
External reference frequency	10 MHz
Input level	-2 dBm to 4 dBm
Input impedance	50 Ohm
Connector type	BNC, female

## Frequency Reference Output

Port	10 MHz Ref Out
Internal reference frequency	10 MHz
Output reference signal level at 50 Ohm impedance	0 dBm to 2 dBm
Connector type	BNC, female

## Trigger Input

Port	Ext Trig In
Input level	
Low threshold voltage	0.8 V
High threshold voltage	2.7 V
Input level range	0 V to + 5 V
Pulse width	≥ 2 µs
Polarity	positive or negative
Input impedance	≥ 10 kOhm
Connector type	BNC, female

## Trigger Output

Port	Ext Trig Out
Maximum output current	20 mA
Output level	
Low level voltage	0.4 V
High level voltage	3.0 V
Polarity	positive or negative
Connector type	BNC, female

## System & Power

Operating system	Windows 7 and above
CPU frequency	1.0 GHz
RAM	512 MB
Interface	USB 2.0
Connector type	USB B
Power supply	110-240 V, 50/60 Hz
Power consumption	45 W

## Factory Adjustment

Recommended factory adjustment interval	3 years
---	---------

## Environmental Specifications

Operating temperature	+5 °C to +40 °C (41 °F to 104 °F)
Storage temperature	-50 °C to +70 °C (-58 °F to 158 °F)
Humidity	90 % at 25 °C (77 °F)
Atmospheric pressure	70.0 kPa to 106.7 kPa