

# Software Release Notes

## CMTVNA

### Version 1.3.0

- Now when program exits, the program window's size and position is saved
- Added channel, diagram and trace maximization capability
- Added "Active Only" property for markers
- Added marker alignment feature
- Added right-click menu for markers
- Added right-click menu for Trace Manager
- Added right-click menu for diagrams
- Added calibration to the quick-access bar located above the diagrams
- Fixed button area of the "Show Only Favorites" button in "Edit Kits" menu
- Now when a marker is enabled, it will be coupled on all traces by default
- Switching between channels in cal set setup now does not change the active channel
- Fixed a bug when saving data in a report
- Fixed a bug with the shortcut's name under the /cmtvna/bin folder
- Fixed a bug with "Show Only Favorites" toggle button's position
- Fixed a bug where when "CALC:PAR:DEF" command is sent when VNA has a marker in tracking mode, the marker stops tracking but menu still shows tracking "on"
- Fixed bugs with Flatness calculation and RF Filter Statistics
- Fixed a bug where after loading certain states, plot has no grid
- Added SCPI command "DISP:WIND:ANN:MARK:SING"

### Version 1.2.2

- Fixed bug with Report button under Save/Recall
- Fixed bug with saving static trace

### Version 1.2.1

- Added demo mode for R and VTR series
- Added USB driver and vc\_redist auto-installation in the installer
- Added capability for saving states in the quick-access slots into file
- Added SCPI Commands:  
CALC:ALLT:DATA:SDAT?  
CALC:ALLT:DATA:FDAT?  
DISP:SHOW  
DISP:HIDE  
DISP:ENAB  
SENS:CORR:COLL:SUBC  
SYST:TIME?  
SYST:RWL

# Software Release Notes

## CMTVNA

SYST:REM

SYST:LOC

- Fixed error reporting when automating calibration. Now error will be reported if not all required measurements are taken before applying calibration
- Fixed USB connection issue with SN09xx VNAs
- Fixed USB connection issue with R180 and RP180
- Fixed acronym for one-path calibrations. Now is back to [OP]
- Fixed default system impedance for RP5 and RP10
- Fixed bug with toggling between “show only favorites” in calibration kit menu
- Fixed bug with deleting connector type in calibration kit menu

### Version 1.2.0

- Added support for VTRM0x02 VNAs
- Added search range setting for peak limit tests and peak limit test SCPI command is modified for it
- Added marker coupling
- Added SCPI command CALC:DATA:XAX?
- Added SCPI command DISP:WIND:TRAC:Y:RLEV:AUTO
- Added SCPI command \*RST

### Version 1.1.0

- First release