COPPER MOUNTAIN® TECHNOLOGIES
631 E New York Street | Indianapolis, IN 46202 USA
www.coppermountaintech.com

Value Series Vector Network Analyzer Specifications



V0402	100 kHz to 4.5 GHz
V0602	100 kHz to 6.5 GHz
V0902	100 kHz to 9 GHz

Revision 26.00 07.07.2026

U.S.: +1.317.222.5400
Latin America: +1.954.495.3459
Singapore: +65.63.23.6546
EMEA: +44 75 03 69 21 13

General Overview

V0402, V0602, and V0902

Frequency range	
V0402	100 kHz to 4.5 GHz
V0602	100 kHz to 6.5 GHz
V0902	100 kHz to 9 GHz
Measured parameters	S11, S21, S12, S22
Sweep types	linear frequency, log frequency, segment, power sweep
Dynamic range	>130 dB typ. (10 Hz IF BW)
Measurement speed	25 µs typ.
Output power adjustment range	-50 dBm to +5 dBm
Measurement points per sweep	up to 500,001

Hardware Specifications

V0402, V0602, & V0902

[1] All specifications subject to change without notice.

Measurement Range

Impedance	50 Ohm
Test port connector	type N, female
Number of test ports	2
Frequency range	
V0402	100 kHz to 4.5 GHz
V0602	100 kHz to 6.5 GHz
V0902	100 kHz to 9 GHz
Full frequency accuracy	$\pm 5 \cdot 10^{-6}$
Frequency resolution	1 Hz
Number of measurement points	2 to 500,001
Measurement bandwidths (with 1/1.5/2/3/5/7 steps)	1 Hz to 300 kHz
Dynamic range[2]	
100 kHz to 10 MHz	115 dB
10 MHz to 4.5 GHz	130 dB (135 dB typ.)
4.5 GHz to 6.5 GHz	125 dB (130 dB typ.)
6.5 GHz to 9.0 GHz	123 dB (130 dB typ.)

[2] The dynamic range is defined as the difference between the specified maximum power level and the specified noise floor. The specification applies at 10 Hz IF bandwidth.

Measurement Accuracy[3]

Accuracy of transmission measurements[4]	Magnitude/Phase
100 kHz to 10 MHz	
0 dB to +10 dB	±0.35 dB / ±3.5°
-35 dB to 0 dB	±0.25 dB / ±2.5°
-55 dB to -35 dB	±0.35 dB / ±3.5°
-75 dB to -55 dB	±1.2 dB / ±8.0°
10 MHz to 4.5 GHz	
0 dB to +10 dB	±0.25 dB / ±2.5°
-50 dB to 0 dB	±0.15 dB / ±1.5°
-70 dB to -50 dB	±0.25 dB / ±2.5°
-90 dB to -70 dB	±1.1 dB / ±7.5°
4.5 GHz to 9 GHz	
0 dB to +10 dB	±0.25 dB / ±2.5°
-45 dB to 0 dB	±0.15 dB / ±1.5°
-65 dB to -45 dB	±0.25 dB / ±2.5°
-85 dB to -65 dB	±1.1 dB / ±7.5°
Accuracy of reflection measurements[5]	Magnitude/Phase
-15 dB to 0 dB	±0.5 dB / ±4°
-25 dB to -15 dB	±1.5 dB / ±10°
-35 dB to -25 dB	±5.5 dB / ±30°
Trace noise magnitude (IF bandwidth 3 kHz)	
100 kHz to 10 MHz	0.005 dB rms
10 MHz to 4.5 GHz	0.002 dB rms
4.5 GHz to 9 GHz	0.004 dB rms
Temperature dependence	0.02 dB/°C

[3] Reflection and transmission measurement accuracy applies over the temperature range of (73 ± 9) °F or (23 ± 5) °C after 30 minutes of warming up, with less than 1°C deviation from the full two-port calibration temperature,at output power of -5 dBm. Frequency points have to be identical for measurement and calibration (no interpolation allowed).

[4] Transmission specification are based on a matched DUT, and IF bandwidth of 10 Hz.

[5] Reflection specifications are based on an isolating DUT.

Effective System Data

100 kHz to 9 GHz	
Directivity	42 dB
Source match	38 dB
Load match	42 dB
Reflection tracking	±0.10 dB
Transmission tracking	
100 kHz to 10 MHz	±0.25 dB
10 MHz to 9 GHz	±0.14 dB

Uncorrected System Performance

100 kHz to 6.5 GHz	
Directivity	15 dB
Source match	15 dB
Load match	15 dB
6.5 GHz to 9 GHz	
Directivity	12 dB
Source match	12 dB
Load match	12 dB

Test Port Output

Power range	
100 kHz to 6.5 GHz	-50 dBm to +5 dBm
6.5 GHz to 9 GHz	-50 dBm to +3 dBm
Power accuracy	±1.5 dB
Power resolution	0.05 dB
Harmonic distortion[6]	-15 dBc
Non-harmonic spurious[6]	-20 dBc

[6] Specification applies over frequency range above 10 MHz, at output power of 0 dBm.

Test Port Input

Noise floor	
100 kHz to 10 MHz	-120 dBm/Hz
10 MHz to 4.5 GHz	-135 dBm/Hz
4.5 GHz to 9 GHz	-130 dBm/Hz
Damage level	+23 dBm
Damage DC voltage	25 V

Measurement Speed

Time per point	25 µs typ.
Port switchover time	1 ms

Frequency Reference Input

Port	10 MHz Ref In/Out
External reference frequency	10 MHz
Input level	-1 dBm to 5 dBm
Input impedance	50 Ohm
Connector type	BNC, female

Frequency Reference Output

Port	10 MHz Ref In/Out
Internal reference frequency	10 MHz
Output reference signal level at 50 Ohm impedance	-1 dBm to 5 dBm
Connector type	BNC, female

Trigger Input

Port	Ext Trig In
Input level	
Low threshold voltage	0.8 V
High threshold voltage	2.0 V
Input level range	0 V to +3.3 V
Pulse width	≥2 µs
Polarity	positive or negative
Input impedance	≥5 kOhm
Connector type	BNC, female

Trigger Output

Port	Ext Trig Out
Maximum output current	12 mA
Output level	
Low level voltage	0.0 V
High level voltage	3.3 V
Polarity	positive or negative
Connector type	BNC, female

System and Power

S2VNA Software	
Operating system (min requirements)	Windows 10 and above
CPU	4 core 2.0 GHz (x64)
RAM	4 GB
CMT VNA Software	
Operating system (min requirements)	Windows 10, Ubuntu 24.04
CPU	4 core 2.0 GHz (x64 or arm64)
RAM	8 GB
Interface	USB 2.0
Connector type	USB C
Input power (VNA)	9 V DC to 15 V DC
Input power consumption (VNA)	26 W
Power supply (Main outlet)	110-240 V, 50/60 Hz
Power consumption (Main outlet)	30 W

Calibration

Recommended factory adjustment interval	3 years

Dimensions

Length	297 mm
Width	160 mm
Height	44 mm
Weight	2.3 kg (70.5 oz)

Environmental Specifications

Operating condition	
Temperature	+5 °C to +40 °C (41 °F to 104 °F)
Humidity	90 % at 25 °C (77 °F)
Storage	
Temperature	+0 °C to +40 °C (32 °F to 104 °F)
Humidity	80 % at 35 °C (95 °F)
Non-operating temperature	-50 °C to +70 °C (-58 °F to 158 °F)
Atmospheric pressure	70.0 kPa to 106.7 kPa

Reflection Accuracy Plots

Reflection Magnitude Errors





Specifications are based on isolating DUT (S21 = S12 = 0)


0.05
0.04
0.03
0.02
0.01
0
Reflection coefficient error, linear
100 kHz to 9 GHz (S21=S12=0)
100 kHz to 9 GHz (S21=S12=1)
0
0.1
0.2
0.3
0.4
0.5
0.6
0.7
0.8
0.9
1
Reflection coefficient, linear

Reflection Phase Errors



Specifications are based on isolating DUT (S21 = S12 = 0)



Transmission Accuracy Plots

Transmission Magnitude Errors







Specifications are based on matched DUT, and IF bandwidth of 10 Hz

Transmission Phase Errors







Specifications are based on a matched DUT, and IF bandwidth of 10 Hz

Transmission Magnitude Errors for Unmatched Devices






4.5 GHz to 9 GHz
S11=S22=0.000 (VSWR=1)
S11=S22=0.333 (VSWR=2)
Transmission coefficient error, dB
1.2
1.1
1
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0
10
0
-10
-20
-30
-40
-50
-60
-70
-80
-90
Transmission coefficient, dB

Transmission Phase Errors for Unmatched Devices







Transmission Errors for Matched Devices vs Output Power and IF Bandwidth

